

Millimeter-Wave Properties of the Atmosphere: Laboratory Studies and Propagation Modeling

Hans J. Liebe
Donald H. Layton



U.S. DEPARTMENT OF COMMERCE
Clarence J. Brown, Acting Secretary

Alfred C. Sikes, Assistant Secretary
for Communications and Information

October 1987

CONTENTS

	Page
ABSTRACT.....	1
1. INTRODUCTION.....	1
2. LABORATORY STUDIES OF MOIST AIR ABSORPTION AT 138 GHz.....	3
2.1 Experimental Arrangement.....	4
2.2 Moist Air Attenuation Measurements	9
2.3 Water Vapor and Moist Air Attenuation Results	13
3. ATMOSPHERIC PROPAGATION MODEL MPM.....	16
3.1 Features of the Program	16
3.2 MPM Calibration.....	19
3.3 Interpretation of H ₂ O Continuum Absorption.....	19
3.4 MPM Predictions.....	21
4. EXPERIMENTAL-VERSUS-MODEL (MPM) DATA.....	28
4.1 Laboratory Measurements.....	32
4.2 Field Measurements.....	32
5. CONCLUSIONS.....	39
6. ACKNOWLEDGMENTS.....	42
7. REFERENCES.....	43
APPENDIX A: THE REFRACTIVE INDEX OF THE NEUTRAL ATMOSPHERE FOR FREQUENCIES UP TO 1000 GHz.....	45
APPENDIX B: PRINTOUT OF MPM-N PROGRAM FOR VERSION A (FREQUENCY PROFILES).....	61

LIST OF FIGURES

	Page
Figure 1. Millimeter wave spectrometer for controlled moist air studies (a) schematic and (b) cell design.....	6
Figure 2. Photograph of millimeter-wave spectrometer.....	7
Figure 3. Mm-wave spectrometer operational data (five temperatures T_i); peak values of reference and reflected signals a_K , and a ; and relative attenuation α_r) for a 1-hour measurement period with an evacuated cell ($f_R = 137.8$ GHz): (a) automatic calibration to $\alpha_r = 0$ dB for changes, $\Delta a_K = 0\text{--}1$ dB; (b) detection stability and sensitivity $(\alpha_{min} \approx 0.006/0.13 \leq 0.05$ dB/km).	10
Figure 4. Temperature responses inside the spectrometer cell: (a) time-response test of gas temperature (T_g) sensors, (b) temperature-vs.-pressure behavior for a typical dry air case.....	12
Figure 5. Mixing effects of $H_2O + Air$ from time series of 138 GHz attenuation: (a) piston effect and diffusion mixing; (b) decompression condensation during pump-down over open vapor source.....	12
Figure 6. Typical raw data plots of relative attenuation $\alpha(P)$ for pressure scans at 137.8 GHz introducing (a) water vapor, $P = e$, and (b) $P = e_1 + p$	17
Figure 7. MPM-predicted specific values of attenuation α and dispersive delay β at sea level height $h = 0$ km ($P=101.3$ kPa, $T=25^\circ$, RH=0 to 100%) over the frequency range, $f = 1$ to 350 GHz. Window ranges are marked W1 to W5.....	22
Figure 8. Water vapor absorption in window ranges for constant relative humidity increments ($\Delta RH = 12.5\%$) at sea level.....	24
Figure 9. Pressure broadening (Air) example of the 183 GHz H_2O line.....	24
Figure 10. Attenuation α and delay rate β for three rain events ($R=10$, 50, and 100 mm/h) added to moist air (RH=95%), sea level condition. Also shown are dry air (0% RH) and moist air (50% RH) characteristics.....	25

Figure 11. Attenuation α and delay β rates for three fog events ($w=0.10$, 0.125 , and 0.5 g/m^3) added to saturated air ($\text{RH}=100\%$) sea level condition. Also shown are dry air (0% RH) and moist air (50% RH) characteristics:	
(a) $f = 1\text{-}1000 \text{ GHz}$	26
(b) $f = 1\text{-}350 \text{ GHz}$	27
Figure 12. Absolute (v) and relative (RH) humidity dependence of attenuation α and delay β at $f = 94 \text{ GHz}$ for various sea level conditions ($P = 101.3 \text{ kPa}$ and $T = -20$ to 40°C)...	29
Figure 13. Two haze cases (A: 1 mg/m^3 and C: 1 mg/m^3) for prefog ($\text{RH}=99\text{-}99.9\%$) and fog ($w=0.1$ and 0.2 g/m^3) conditions at three temperatures (0 , 10 , 20°C) displaying the associated attenuation α and delay β rates at $f = 220 \text{ GHz}$	30
Figure 14. Pressure profiles at $f = 138 \text{ GHz}$ simulating the laboratory attenuation measurements presented in Section 2.3	31
Figure 15. Moist air attenuation α across the atmospheric window ranges W5 and W6 (320 to 430 GHz) at temperatures 8.5 , 25.5 and 32.9°C : data points [21], [22]; solid lines MPM	35
Figure 16. Moist air attenuation $\alpha(v)$ measured at 96.1 GHz over a 21.4 km line-of-sight path located in Huntsville, AL ($h \approx 0.3 \text{ km}$) for six temperature groups between 2.5 and 37.5°C [19]: data points are 5-min averages for 4.5 days (5/4-6, 8/15-16/1986); solid lines, MPM	36
Figure 17. Water vapor attenuation rates $\alpha(v)$ across the atmospheric window range W4 at four temperatures, 5 , -7 , -10 , -18°C : data points [20]; solid lines, MPM	37
Figure 18. Terrestrial path attenuation at 94 GHz and $0.65 \mu\text{m}$ (visible light) under nonprecipitating conditions as a function of absolute (v) and relative (RH) humidity [3]: (a) data points, 5-min averages taken every 30 min during a period of 4 months [23]; (b) MPM simulation of (a) for absolute humidity; (c) MPM simulation of (a) over the range, RH=95 to 100%, including haze model C	38
Figure 19. Correlated vertical atmospheric noise temperatures T_A at the frequency pairs $10/33$, $10/90$, and $33/90 \text{ GHz}$. Path-integrated water vapor is $V = \int v dh$, mm. The measurements were conducted from two sites located at height levels $h_0=0.25$ and 3.30 km : data points [24]; solid lines, MPM with a mean July height profile (0-30 km) of P , T , and RH for San Francisco, CA [3].....	40

Page

- Figure A-1. Moist air refractivity $N = N' - jN''$ for sea level condition (P,T) and various relative humidities (RH) over the frequency range from 0 to 1000 GHz 58
- Figure A-2. Moist air attenuation (α) and delay (β) rates for a sea level condition (P,T) and various relative humidities (RH) over the frequency range from 1 to 1000 GHz 60

LIST OF TABLES

	Page
Table 1. Comparison between Measured (X) and Model-Predicted (M=MPM, see Section 3) Coefficients $k_{s,f}$ of (5). Experimental conditions: $f = 137.8 \text{ GHz}$, $T = 282\text{-}316 \text{ K}$, $P = e_1 + p$, $p = 0\text{-}110 \text{ kPa}$	14
Table 2. Attenuation Measurements of Water-Vapor/Air-Constituent Mixtures ($f=137.8 \text{ GHz}$, $T=303 \text{ K}$, $e_1=3.80$ and $p=0\text{-}100 \text{ kPa}$) Expressed with k_x -Coefficients of (5), and Corresponding Broadening Efficiencies m_x (6). Included are Line-Core Measurements m_l and their Predictions m_1 and k_1 Transposed to 138 GHz	15
Table 3. Summary Data of H_2O line Spectrum and H_2O Excess Attenuation at 137.8 GHz, $T = 300 \text{ K}$	20
Table 4. Reported Data on $(\text{H}_2\text{O})_2$ Dimer Concentration e_D/e over the Temperature Range for 300 to 386 K	20
Table 5. Measured (EXP) and Predicted (MPM) Dispersion in Dry Air at 300 K (Interference Coefficients from Rosenkranz [10])....	33
Table 6. Comparison between MPM-Predicted and Experimental Attenuation for Water Vapor (e) and Moist Air ($P = e_1 + p$) in the Wing Region of the H_2O Line Centered at $v_0 = 183.310 \text{ GHz}$	34
Table A1. Frequency Profiles of Atmospheric Complex Refractivity	57
Table A2. Frequency Profiles of Attenuation and Delay Rates	59

